

## Pneumatic strapping tool for polypropylene and polyester strap with vibration sealing



New cooling welding time indicator



### TECHNICAL SPECIFICATIONS

#### DIMENSIONS

Length	280 mm • 11"
Width	150 mm • 6"
Height	175 mm • 6.9"
Weight	4.9 Kgs • 10.8 lbs

#### FEEDING

Pressure range	4.5 -7 bar / 64-99 psi
Air consumption	14 L/s - 29 cuft/min

#### PERFORMANCE

Max. tension force	2500 N - 6.5 bar- 92psi (variable with friction)
Tensioning speed	11 mt/m
Sealing	Vibration sealing
Joint strength	80% of breaking strength*
Gear ratio	-

\* variable according to strap type  
 \*\* only with friction on tensioning

### MODEL

CODE	TYPE	STRAP	THICKNESS
T101013	ITA10 / 10mm **	PP-PET	0.4-1.2 mm 0.016"-0.047"
		10 mm • 3/8"	
T101313	ITA10 / 13mm **	PP-PET	0.4-1.2 mm 0.016"-0.047"
		13 mm • 1/2"	
T109913	ITA10 / 16-19mm **	PP-PET	0.4-1.2 mm 0.016"-0.047"
		16-19 mm • 5/8"-3/4"	

#### POLYESTER STRAP



#### POLYESTER STRAP



#### POLYPROPYLENE STRAP



**Pakmak Ambalaj Paketleme Makineleri**  
 10016 Sk. No.6 AOSB Çiğli / İzmir  
 0 232 328 10 51  
 info@pakmak.com

