

PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS

DIMENSIONS

Length	350mm • 13.8"
Width	140 mm • 5.5"
Height	170 mm • 6.7"
Weight	4 Kgs • 8.8 lbs

FEEDING

Pressure range	5.5 - 7 bar / 78-99 psi
Air consumption	12 L/s - 25 cuft/min

PERFORMANCE


Max. tension force	3000N - 4500N -6.5bar-92psi
Tensioning speed	5mt/m 4500N - 7mt/m 3000N
Sealing	Seal single notch
Joint strength	80% of breaking strength*
Gear ratio	-

* variable according to strap type

MODEL

CODE	TYPE	STRAP	THICKNESS
T401311	ITA40 - 13mm-1/2"-2000N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401611	ITA40 - 16mm-5/8"-2000N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401911	ITA40 - 19mm-3/4"-2000N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401321	ITA40 - 13mm-1/2"-5500N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401621	ITA40 - 16mm-5/8"-5500N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401921	ITA40 - 19mm-3/4"-5500N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401331	ITA40 - 13mm-1/2"-7500N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401631	ITA40 - 16mm-5/8"-7500N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm
T401931	ITA40 - 19mm-3/4"-7500N	R 850N/mm ²	0.4mm - 0.8mm
		R 1100N/mm ²	0.4mm - 0.63mm

SEAL SINGLE NOTCH



Endüstriyel Paketleme
Sistemleri

www.pakmak.com