

BATTERY STRAPPING TOOL FOR POLYESTER STRAP WITH VIBRATION SEALING



NEW

ONE PUSH OPERATED

TECHNICAL SPECIFICATIONS

DIMENSIONS

Length	300 mm • 11.8"
Width	150 mm • 5.9"
Height	160 mm • 6.3"
Weight	4,1 Kgs • 9 lbs

FEEDING

Battery	14.8V-3.2 A/h LI-PO
---------	---------------------

PERFORMANCE

Max. tension force	5500N
Tensioning speed	12mt/m
Sealing	Vibration sealing
Joint strength	80% of breaking strength*

* variable according to strap type

OPERATING MODES

- Fully Automatic
- Semi Automatic
- Manual

With Fully Automatic Mode tensioning, welding and strap cutting are performed with only one push of a button.

MODEL

CODE	TYPE	STRAP	THICKNESS
T259997	ITA25 / 16-19mm with one battery	PET 16 mm-5/8"	1.05 mm - 0.041"
		PET 19 mm-3/4"	0.8 mm - 0.031" ÷ 1,27 mm - 0.05"
T2599971	ITA25 / 16-19mm with one battery and charger	PET 16 mm-5/8"	1.05 mm - 0.041"
		PET 19 mm-3/4"	0.8 mm - 0.031" ÷ 1,27 mm - 0.05"
T2599972	ITA25 / 16-19mm with two batteries and charger	PET 16 mm-5/8"	1.05 mm - 0.041"
		PET 19 mm-3/4"	0.8 mm - 0.031" ÷ 1,27 mm - 0.05"

POLYESTER STRAP



POLYESTER STRAP

